

Product Data Sheet (2020-07-27)

ENA 7 - 30

For active degassing and automatic topping up of closed heating and cooling systems. The ENA is a pressure step degasser that makes use of vacuum for highly efficient degassing of closed systems. Moreover, the ENA ensures automatic topping-up of the system after the top-up water has been degassed.

Can be easily used in combination with a Flexcon diaphragm pressure expansion vessel or pressure expansion automat.



Type	Max. work. press. [bar]	Operating pressure [bar]	Syst. conn.	Dimensions			Weight [kg]	###	Order Code
				W. [mm]	D. [mm]	H. [mm]			
ENA 7	8	0.8 - 2.7	Rp 1"	740	325	1270	40	1	17070
ENA 10	8	0.8 - 3.5	Rp 1"	740	325	1270	40	1	17090
ENA 20	8	2.0 - 4.5	Rp 1"	740	325	1270	45	1	17091
ENA 30	10	3.0 - 8.0	Rp 1"	710	525	1270	60	1	17092



Advantages

- Active degassing by patented PALL-Ring technology.
- The menu of the control unit is available in 18 languages.
- Easy to use.
- Fully assembled and ready to connect.
- Compact and robust design.
- Controller can be programmed as required. Connection to BMS possible (RS 485).

Technical information

- Working temperature: 3 °C to 70 °C.
- Maximum (feed) supply temperature in the system: 120 °C.
- Ambient temperature: > 3 °C to 45 °C.
- Maximum pressure in the suppletion feed line: 2 to 8 bar.
- Noise production: approx. 55 dB(A).
- Electrical connection 230 V 50 Hz.
- Suitable for addition of glycol-based anti-freeze up to 30%.
- Complies with the following guidelines:

Machinery Directive 2006/42/EC.
PED 2014/68/EU.



Flamco

Find more information online:

[Manuals](#)

[Certificates](#)

[CAD drawings](#)

[Extra documentation](#)

[Animations](#)

Flamco Group

Plotterweg 31

3821 BB, Amersfoort - nl

T +31 33 299 75 00

F +31 33 298 64 45

E info@flamcogroup.com

I <https://flamcogroup.com>